



CONTENTS

| | _11111_ | |
|--|---------|--|

| Innovative and Practical Solutions | 2-3 |
|--|-------|
| High Performance and Aesthetic Solutions | 4-5 |
| Technology and Art Compliant Solutions | 6-7 |
| E-Line Smart STD-I Standard Free Type | 8-9 |
| E-Line Smart LUX-I Luxury Free Type | 10-11 |
| E-Line Smart LUX-II Luxury Mounted Type | 12-13 |
| E-Line Smart IN-I Embedded Rectangular Type | 14-15 |
| E-Line Smart IN-II Embedded Cylindirical Type | 16-17 |
| E-Line Smart SM-K / SM-MK Cylindrical Column Type | 18-19 |
| Technical Specifications and Order Codes | |
| Standard Empty Product Table | 20 |
| Equipment Table For Standard Products | 21 |
| E-Line Smart SM-LUX I Free Type / Smart SM-LUX II Mounted Type | 22 |
| E-Line Smart SM-STD I / Standard Free Type | .23 |
| E-Line Smart SM-IN I / Embedded Rectangular Type | .24 |
| E-Line Smart SM-IN II / Embedded Cylindirical Type | .25 |
| E-Line Smart SM-MK / Cylindrical Column Type | .26 |
| Cable Organizer | 27 |
| Dual USB Charging Device | .28 |
| Socket Modules | 29-30 |
| General Structure and Product Specifications | 31 |
| Declaration | 32 |
| Design Form | 33 |

►► INNOVATIVE AND PRACTICAL SOLUTIONS











►ELEGANT AND PRACTICAL SOLUTIONS FOR BUSINESS CENTERS, OFFICES AND WORKING SPACES

- Off-the-shelf products ready for use and equipped with power (mains/ ups), data, telephone and multimedia sockets for desk jobs, meetings and presentations.
- Ergonomic and flexible design that can be fitted with modular type energy, weak current and multimedia sockets based on your personal needs and choices.

► ANODIZED COATED ALUMINIUM BODY

- Colour options include anodized coating, white and black.
- Rich visual and functional options based on your personal needs and choices.

►► HIGH PERFORMANCE AND AESTHETIC SOLUTIONS












▶FUNCTIONAL AND FLEXIBLE DESIGN

- Structure and flexibility that can be managed in line with needs and demands.
- A wide range of cable entries and termination ends.
- Cable entries with blasting; bushed or screwless interlocking socket type.
- Structure ready for use thanks to interior connection structure and cabled and screwless connector/electric terminal.

▶INDISPENSABLE COMMUNICATION NEEDS

- Structural and accessorial options in harmony with the work environment.
- Aesthetic and high performance body structure.


▶►TECHNOLOGY AND ART COMPLIANT SOLUTIONS











▶INNOVATIVE, AESTHETIC AND ARTISTIC

- May be embedded into the desk or working surfaces.
- A product variety backed by fixing holder without any worry for aesthetic look.

▶TECNOLOGICAL & SAFELY

- Product selections with optional exclusively designed box equipped with miniature circuit breaker (MCB), residual current device (RCD) or Residual Current Circuit Breaker with Over Current Protection (RCBO).
- Raw material used in all plastic parts in our products is polycarbonate (PC) and is halogen free and is within V0 flame retardant class according to UL 94 standard.
- When used for computers, TV or electronic devices, complete protection with an optional overcurrent protection device in order to protect the devices from current fluctuations.



ELINESMART SM-STD I

▶STANDARD FREE TYPE



- The structure with its highlighted aesthetics and visual aspects for table top utilization, it is an office automation socket block that can be equipped with 45-degree angled sockets with modular type.
- Upon request, it may be equipped with 2-module miniature circuit breaker with switch or Residual Current Circuit Breaker with Over Current Protection.
- It is manufactured as 6, 8 and 10 module body and utilized with 6 different socket option.
- Our standard type products are manufactured with "MULTI HOLE TYPE" cover, cable holding clamp and spring terminal. For "INTERLOCKING TYPE TERMINAL" and "CABLE GLAND" types please contact us.
- For standard products, you may select the ones that suit your needs on page 26.
- For your requests for products equipped with socket options other than standard products, you can determine such strong current, weak current and multimedia sockets at your option from the "Socket Modules" page.

CABLE ENTRY COVERS:



Multi Hole Type Ø7 Hole (6 Quantity) Ø12 Hole (2 Quantity)



Screwless Type With Snap-On Connector Ø7 Hole (4 Quantity)



Double Cable Gland Type M16x1,5 Hole (2 Quantity)



(4) Single Cable Gland Type 1 M16 x 1,5 Bush



(5) Single Cable Gland Type 2 M20 x 1,5 Bush



(6) Single Cable Gland Type 3 M25 x 1,5 Bush

- ■Please specify the cover type. Standard type products are manufactured with "Multi Hole Type" covers.
- ■Please call us for other cover types.



■E-Line Smart STD I equipped with MCB and/ or RCBO





ELINESMART SM-LUX I

▶►LUXURY FREE TYPE



- The structure with its highlighted aesthetics and visual aspects for table top utilization, it is an office automation socket block that can be equipped with 45-degree angled sockets with modular type.
- Multi hole type side covers for cable entries.
- · Our standard type products are manufactured with cable holding clamp and spring terminal.
- For standard products, you may select the ones that suit your needs on page 22.
- For your requests for products equipped with socket options other than standard products, you can determine such power, weak current and multimedia sockets at your option from the "Socket Modules" page.







ELINESMART SM-LUX II

▶▶LUXURY MOUNT TYPE



- The structure with its highlighted aesthetics and visual aspects for table top utilization, It can be easily fixed to the table edge with its special foot design, it is an office automation socket block that can be equipped with 45-degree angled sockets with modular type.
- Multi hole type side covers for cable entries.
- · Our standard type products are manufactured with cable holding clamp and spring connector.
- For standard products, you may select the ones that suit your needs on page 22.
- For your requests for products equipped with socket options other than standard products, you can determine such power, weak current and multimedia sockets at your option from the "Socket Modules" page.







ELINESMART SM-IN I

▶BUILT-IN RECTANGULAR TYPE



- For flush type with rectangular cross section, an office automation block that can be equipped modular and 45-degree angled sockets required for work environments.
- The cover automatically flaps open with a single press only; it may be used thanks to its special lock mechanism and brush cover structure.
- Our standard type products are manufactured with cable holding clamp and spring terminal.
- Its mounting is quite easy thanks to specially developed side locking that are automatically positioned.
- For standard products, you may select the ones that suit your needs on page 24.
- For your requests for products equipped with socket options other than standard products, you can determine such power, weak current and multimedia sockets at your option from the "Socket Modules" page.








ELINESMART SM-IN II

▶▶FLUSH CYLINDRICAL TYPE




- It is an office automation block that is utilized with 6 different model selections, equipped with modular sockets required for cylindrical working environments with flush mounted circular cross sections.
- The cover is opened automatically with a single press. Thanks to its special lock and tab mechanism and moving head piece, you can use while it is closed.
- PC mounting mechanism allows the easy installation of the cylindrical structure grey anodic coated aluminium body inside the desk.
- Our standard type products are manufactured with cable holding clamp and spring terminal.
- It is manufactured as 6 and 8 module body and utilized with 6 different socket option.

Desk Hole Diameter









ELINESMART SM-K / SM-MK

▶►CYLINDRICAL COLUMN TYPE






- If high and weak current wiring cannot be moved from the flooring or the walls, this "column type" office block with its cylindric form that can carry any energy, phone, data and multimedia sockets, which can be used to lower the cables coming from the suspended ceiling to the table level.
- It can be affixed with special connection parts between the ceiling and the flooring, for short lengths that cannot reach the ceiling, it can be affixed only on the flooring and can be utilized with 45 degree sockets with required modular types.
- The maximum length may be up to 600 cm and special orders may be produced based on the height of the ceiling.
- For shorter versions that are mounted affixed to the floor (max. 120 cm) special orders may be produced based on utilization (table height).
- For products that will be used between the ceiling and the flooring, the in-product high current cables are terminated at the upper section clamps. Phone, data and multimedia cables are laid through the specified cable input holes and may be extended to the sockets
- In standard production, it is offered with 6 different sockets equipped.

▶▶STANDARD PRODUCTS

▶STANDARD EMPTY PRODUCT TABLE





DESCRIPTIONS

- 1.It is manufactured without any sockets from 6 to 20 module in 8 different dimensions as standard, you can also mount the required amount and type of sockets and complete the cabling process.
- 2. Manufactured and sold as empty body. Our company does not complete socket mounting and cabling, and electric tests and therefore will not be held liable in an event of a failure.
- 3. Halogen-Free" PC/ABS side covers with multi holes for cabling and in align with the body type, the screwed cable holding clamps inside the product body and grounding terminal mounted on the body are provided with the product as standard
- 4. In addition to the standard lengths specified in the list, customised products may be manufactured based on request. Please contact us for details.
- 5. Featuring a modular type 45x45 mm or 22.5x45 mm grid and UPS power sockets and suitable for phone, data, USB, HDMI and VGA multimedia socket mounting, the socket height and aluminum profile fitting details may be different based on the brands and may experience incompatibilities, please contact us prior to order.
- 6.2 (two) year warranty against production faults.

▶E-Line Smart SM-STD B / Standard Empty Type

| Product Definition and Picture | Item No | Capacity (Module) Socket | Color | Order Code |
|--------------------------------|---------|-----------------------------|-------|------------|
| | 1 | 6 | | 3178192 |
| | 2 | 8 | | 3178193 |
| | 3 | 10 | | 3178194 |
| | 4 | 12 | Grey | 3178195 |
| | 5 | 14 | orey | 3178196 |
| | 6 | 16 | | 3178197 |
| | 7 | 18 | | 3178198 |
| | 8 | 20 | | 3178199 |
| | 1 | 6 | | 3179211 |
| | 2 | 8 | | 3179212 |
| | 3 | 10 | | 3179213 |
| | 4 | 12 | White | 3179214 |
| | 5 | 14 | Winte | 3179215 |
| | 6 | 16 | | 3179216 |
| | 7 | 18 | | 3179217 |
| | 8 | 20 | | 3179218 |
| | 1 | 6 | | 3179219 |
| | 2 | 8 | | 3179220 |
| | 3 | 10 | | 3179221 |
| | 4 | 12 | Black | 3179222 |
| The second second | 5 | 14 | Didok | 3179223 |
| | 6 | 16 | | 3179224 |
| | 7 | 18 | | 3179225 |
| | 8 | 20 | | 3179226 |

▶▶STANDARD PRODUCTS

▶EQUIPMENT TABLE FOR STANDARD PRODUCTS





DESCRIPTIONS

- 1. Energy sockets are NE-AD. Please contact us for different brands.
- 2. In standard products data (CAT-6, UTP, RJ45) and telephone (Cat-3, RJ11) sockets are not included and these are only provided as "Face Plate".
- 3. Upon request, active and passive network products are ICS brand.. Please contact us for different brands.
- 4. The prices include mounting, internal cabling (for energy sockets) and multi hole type plastic side covers, the cables are "halogen-free". For customized cross sections and types, contact us.
- 5. Products are packaged nylon bags and cardboard boxes.
- 6. Products are under our 2 (two) year warranty against installation defects.
- 7. Our manufacture line also includes special products with any content and size based on your choices in addition to listed standard products.
- 8. In a capacity (module) definition, the first number refers to sockets while the second number refers to aluminium casing.

►ADJUSTABLE DESK MOUNTING MATERIAL



| Product description | Order Code |
|-------------------------------------|---------------|
| SM-LUX II DESK MOUNTING KIT (GREY) | 2086359 |
| SM-LUX II DESK MOUNTING KIT (WHITE) | 2086360 |
| SM-LUX II DESK MOUNTING KIT (BLACK) | 2086361 |

Note: It should be ordered separately if needed. Suitable for SM-LUX II model.



▶DESK FIXING MATERIAL



Order Code : **3048968**

Note: It should be ordered separately if needed. Suitable for SM-LUX I model.



▶ANGLED DESK MOUNTING MATERIAL



Order Code : **2080760**

For SM-STD I model SM-STD I

Note: It should be ordered separately if needed. Suitable for SM-STD I model.

▶▶STANDARD PRODUCTS

▶E-Line Smart SM-LUX I Free Type / Smart SM-LUX II Mount Type





| Product Definition and Picture | | | Capacity | Pow | er Soc | kets | Ac | tive Ne | etwork | Produ | cts | Pass | ive Netv | ork Pro | ducts | | Order Code | Order Code |
|--------------------------------|-------------------------|---------|-----------------------------|-------|--------|------------|------------------|------------------|----------------------|----------------------|-----|-----------------------|---------------------|------------------------|----------------------|-------|--------------------------|-------------------------------|
| SM-LUX I Free Type | SM-LUX II Mount Type | Item No | (Module) socket/ case | Mains | NPS | USB Charge | CAT6 UTP RJ45 | CAT3 UTP RJ11 | USB Adap. 22,5x45 | VGA Adap. 22,5x45 | | Face Plate 22,5x45 | Face Plate 45x45 | Blind Cover 22,5x45 | Blind Cover 45x45 | Color | SM-LUX I Free Type | SM-LUX II Mount Type |
| 10 | A Da | 1 | 8/14 | 1 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3178200 | 3179251 |
| | | 2 | 10/16 | 2 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3178201 | 3179620 |
| | | 3 | 12/18 | 2 | 2 | - | - | - | - | - | - | 4 | - | - | - | Grey | 3178202 | 3179621 |
| | | 4 | 14/20 | 3 | 3 | - | - | - | - | - | - | 2 | - | - | - | 5 | 3178203 | 3179622 |
| | | 5 | 16/22 | 2 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3178204 | 3179623 |
| 1 | | 6 | 18/24 | 3 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3178205 | 3179624 |
| 9 10 | 100.00 | 1 | 8/14 | 1 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179227 | 3179625 |
| | | 2 | 10/16 | 2 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179228 | 3179626 |
| 8 | 1 3 | 3 | 12/18 | 2 | 2 | - | - | - | - | - | - | 4 | - | - | - | White | 3179229 | 3179627 |
| | | 4 | 14/20 | 3 | 3 | - | - | - | - | - | - | 2 | - | - | - | W | 3179230 | 3179628 |
| | | 5 | 16/22 | 2 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3179231 | 3179629 |
| _ | | 6 | 18/24 | 3 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3179232 | 3179630 |
| | | 1 | | 1 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179233 | 3179631 |
| | | 2 | 10/16 | 2 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179234 | 3179632 |
| | 7 | 3 | 12/18 | 2 | 2 | - | - | - | - | - | - | 4 | - | - | - | 쑹 | 3179235 | 3179633 |
| | 202 | 4 | 14/20 | 3 | 3 | - | - | - | - | - | - | 2 | - | - | - | Black | 3179236 | 3179634 |
| | | 5 | 16/22 | 2 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3179237 | 3179635 |
| | | 6 | 18/24 | 3 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3179238 | 3179636 |

▶E-Line Smart SM-LUX I Technical Structure And Dimensions



| SM STD I Standard Free Type Product Dimensions | | | | | | | | | | | | |
|--|----------------|---------|--------|-------|-------------------------|-----|--|--|--|--|--|--|
| Pro | oduct Order Co | de | Module | Produ | Product Dimensions (mm) | | | | | | | |
| A.Coating | White | Black | Module | Α | В | С | | | | | | |
| 3178200 | 3179227 | 3179233 | 8/14 | 355 | 67,5 | 107 | | | | | | |
| 3178201 | 3179228 | 3179234 | 10/16 | 400 | 67,5 | 107 | | | | | | |
| 3178202 | 3179229 | 3179235 | 12/18 | 445 | 67,5 | 107 | | | | | | |
| 3178203 | 3179230 | 3179236 | 14/20 | 490 | 67,5 | 107 | | | | | | |
| 3178204 | 3179231 | 3179237 | 16/22 | 535 | 67,5 | 107 | | | | | | |
| 3178205 | 3179232 | 3179237 | 18/24 | 580 | 67.5 | 107 | | | | | | |





Body: Aluminium

Side Covers: PC/ABS (Polycarbonate), V2 (Flame Retardant Class), HF (Halogen Free)

■ Note: Same as SM-LUX II Mounted Type product dimensions.

22

▶▶STANDARD PRODUCTS

▶E-Line Smart SM-STD I / Standard Free Type




| | | Capacity | Pow | er So | kets | Ac | tive Ne | twork | Produ | icts | Pass | ive Netw | ork Pro | ducts | | |
|--------------------------------|-------|-----------------------------|-------|-------|------------|------------------|------------------|----------------------|----------------------|----------------------|-----------------------|---------------------|------------------------|----------------------|-------|---------------|
| Product Definition and Picture | Mains | (Module) socket/ case | Mains | NPS | USB Charge | CAT6 UTP RJ45 | CAT3 UTP RJ11 | USB Adap. 22,5x45 | VGA Adap. 22,5x45 | HDMI Adap. 22,5x5 | Face Plate 22,5x45 | Face Plate 45x45 | Blind Cover 22,5x45 | Blind Cover 45x45 | Color | Order Code |
| | 1 | 8/14 | 1 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3178185 |
| 5 | 2 | 10/16 | 2 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3177541 |
| 11 | 3 | 12/18 | 2 | 2 | - | - | - | - | - | - | 4 | - | - | - | Grey | 3178188 |
| | 4 | 14/20 | 3 | 3 | - | - | - | - | - | - | 2 | - | - | - | Ē | 3178189 |
| | 5 | 16/22 | 2 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3178190 |
| | 6 | 18/24 | 3 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3178191 |
| | 1 | 8/14 | 1 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179239 |
| 77 | 2 | 10/16 | 2 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179240 |
| 01 | 3 | 12/18 | 2 | 2 | - | - | - | - | - | - | 4 | - | - | - | White | 3179241 |
| ELL IT | 4 | 14/20 | 3 | 3 | - | - | - | - | - | - | 2 | - | - | - | Α̈́ | 3179242 |
| | 5 | 16/22 | 2 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3179243 |
| | 6 | 18/24 | 3 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3179244 |
| | 1 | 8/14 | 1 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179245 |
| | 2 | 10/16 | 2 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179246 |
| 1 - 30 W | 3 | 12/18 | 2 | 2 | - | - | - | - | - | - | 4 | - | - | - | 쑹 | 3179247 |
| | 4 | 14/20 | 3 | 3 | - | - | - | - | - | - | 2 | - | - | - | Black | 3179248 |
| | 5 | 16/22 | 2 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3179249 |
| | 6 | 18/24 | 3 | 4 | - | - | - | - | - | - | 4 | - | - | - | | 3179250 |


■ Note: If necessary, it can be used with "ANGLED DESK MOUNTING MATERIAL". Please see page 21.

▶E-Line Smart SM-STD I / Standard Free Type Technical Specifications



| SM STD I Standard Free Type Product Dimensions | | | | | | | | | | | |
|--|----------------|---------|--------|-------------------------|----|----|--|--|--|--|--|
| Pro | oduct Order Co | de | Module | Product Dimensions (mm) | | | | | | | |
| A.Coating | White | Black | Module | Α | В | С | | | | | |
| 3178185 | 3179239 | 3179245 | 8/14 | 355 | 60 | 55 | | | | | |
| 3177541 | 3179240 | 3179246 | 10/16 | 400 | 60 | 55 | | | | | |
| 3178188 | 3179241 | 3179247 | 12/18 | 445 | 60 | 55 | | | | | |
| 3178189 | 3179242 | 3179248 | 14/20 | 490 | 60 | 55 | | | | | |
| 3178190 | 3179243 | 3179249 | 16/22 | 535 | 60 | 55 | | | | | |
| 3178191 | 3179244 | 3179250 | 18/24 | 580 | 60 | 55 | | | | | |





Body: Aluminium

Side Covers: PC (Polycarbonate), V0 (Flame Retardant Class), HF (Halogen Free)

▶▶STANDARD PRODUCTS

▶E-Line Smart SM-IN I / Embedded Rectangular Type



| | Product Definition and Picture | | Capacity Power Sockets Active Network Products Passive Network Products | | | | | | | ducts | | | | | | | |
|--|--------------------------------|---|---|-------|-----|------------|------------------|------------------|----------------------|----------------------|----------------------|-----------------------|---------------------|------------------------|----------------------|-------|---------------|
| | | | (Module) socket/ case | Mains | NPS | USB Charge | CAT6 UTP RJ45 | CAT3 UTP RJ11 | USB Adap. 22,5x45 | VGA Adap. 22,5x45 | HDMI Adap. 22,5x5 | Face Plate 22,5x45 | Face Plate 45x45 | Blind Cover 22,5x45 | Blind Cover 45x45 | Color | Order Code |
| | _ | 1 | 8/14 | 1 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3177542 |
| | | 2 | 10/16 | 2 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3178181 |
| | 100 | 3 | 12/18 | 2 | 2 | - | - | - | - | - | - | 4 | - | - | - | Grey | 3179252 |
| | | 4 | 14/20 | 3 | 3 | - | - | - | - | - | - | 2 | - | - | - | | 3179253 |
| | | | | | | | | | | | | | | | | | |



| 1 | 8/14 | 1 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179256 |
|---|-------|---|---|---|---|---|---|---|---|---|---|---|---|-------|---------|
| 2 | 10/16 | 2 | 2 | - | - | - | - | - | - | 2 | - | - | - | ite | 3179257 |
| 3 | 12/18 | 2 | 2 | - | - | - | - | - | - | 4 | - | - | - | White | 3179258 |
| 4 | 14/20 | 3 | 3 | - | - | - | - | - | - | 2 | - | - | - | | 3179259 |




| 1 | 8/14 | 1 | 2 | - | - | - | - | - | - | 2 | - | - | - | | 3179262 |
|---|-------|---|---|---|---|---|---|---|---|---|---|---|---|-------|---------|
| 2 | 10/16 | 2 | 2 | - | - | - | - | - | - | 2 | - | - | - | Black | 3178183 |
| 3 | 12/18 | 2 | 2 | - | - | - | - | - | - | 4 | - | - | - | Bla | 3179263 |
| 4 | 14/20 | 3 | 3 | - | - | - | - | - | - | 2 | - | - | - | | 3179264 |

▶E-Line Smart SM-IN I / Embedded Rectangular Type Technicial Specifications




| | SM IN I Embedded Rectangular Type Technicial Specifications | | | | | | | | | | | | | |
|-----------|---|---------|--------|-----|--------|-------|---------|-----|-----------|------------|--|--|--|--|
| Pro | duct Order Co | ode | Module | Pro | duct D | imens | ions (n | nm) | Cross-Sec | ction Dim. | | | | |
| A.Coating | White | Black | woule | Α | В | С | D | E | F | G | | | | |
| 3177542 | 3179256 | 3179262 | 8/14 | 355 | 120 | 102 | 335 | 97 | 337 | 102 | | | | |
| 3178181 | 3179257 | 3178183 | 10/16 | 400 | 120 | 102 | 380 | 97 | 382 | 102 | | | | |
| 3179252 | 3179258 | 3179263 | 12/18 | 445 | 120 | 102 | 425 | 97 | 427 | 102 | | | | |
| 3179253 | 3179259 | 3179264 | 14/20 | 490 | 120 | 102 | 470 | 97 | 472 | 102 | | | | |



Body: Aluminium **Side Covers**: PC/ABS, V2 (Flame Retardant

Class) HF (Halojen Free)



▶►TECHNICAL STRUCTURE AND DIMENSIONS

▶E-Line Smart SM-IN II / Embedded Cylindirical Type



| | EC | QUIPMENT TABLE FOR | STANDARD PRODUCTS |
|----|------------|-------------------------------|--|
| No | Order Code | Model | Equipment |
| 1 | 3179195 | SM-IN II 6 Module | 1 MAINS+1 UPS+2 DATA PHONE FACE PLATE |
| 2 | 3177543 | SM-IN II 8 Module (Type-1) | 1 MAINS+2 UPS+2 DATA PHONE FACE PLATE |
| 3 | 3178184 | SM-IN II 8 Module (Type-2) | 2 MAINS+1 UPS+2 DATA PHONE FACE PLATE |
| 4 | 3179197 | SM-IN II 8 Module (Type-3) | 1 MAINS+1 UPS+2 DATA PHONE FACE PLATE 1 USB CHARGE + 1 VGA ADAPTER |
| 5 | 3179198 | SM-IN II 8 Module (Type-4) | 1 MAINS+1 UPS+2 DATA PHONE FACE PLATE 1 USB CHARGE + 1 HDMI ADAPTER |
| 6 | 3179200 | SM-IN II 8 Module (Type-5) | 1 MAINS+1 UPS+2 DATA PHONE FACE PLATE 1 USB CHARGE +1 USB ADAPTER |

[•]EQUIPMENT DESCROPTIONS IN STANDARD PRODUCTS SECTION (PAGE 21) ARE ALSO APPLICABLE HERE.


IMPORTANT NOTE:

The electricity wiring shall be thin and multiple wire (flexible), multi-core, LSoH type (052XZ1-F 300/500V) and cable at a sufficient length shall be left to compensate the upward-downward movement of the profile body holding the sockets.





■ Grey Anodic Coated Body (Plastic part in black)

▶E-Line Smart SM-IN II / Embedded Cylindirical Type Technical Structure



| SM IN | I II Embed | ded Cylindirio | al Type Product | Dimensions |
|-------------------|------------|----------------|-----------------|------------------------|
| Product Or | der Code | Product Dir | nensions (mm) | Cross- Section Dim. |
| A.Coating | Module | Н | B(DIAM) | D (mm) |
| 3179195 | 6 | 280 | 126 | 112 |
| 3177543 | 8 | 330 | 126 | 112 |
| 3178184 | 8 | 330 | 126 | 112 |
| 3179197 | 8 | 330 | 126 | 112 |
| 3179198 | 8 | 330 | 126 | 112 |
| 3179200 | 8 | 330 | 126 | 112 |







Body: Aluminium


Side Covers: PC/ABS, V2 (Flame Retardant Class), HF (Halojen Free)

Cover: PC/ABS, V2 (Flame Retardant Class), HF (Halojen Free) + 304 Stainless

▶►TECHNICAL STRUCTURE AND DIMENSIONS

▶E-Line Smart SM-MK / Cylindrical Column Type






| | | MINI COLUMN TY | PE STANDARD PRODUCT HARDWARE TABLE | | |
|----|------------|-----------------------------|---|-----------|-----------|
| No | Order Code | Model | Equipment | A (mm) | B (mm) |
| 1 | 3179201 | SM-MK 6 Module | 1 MAINS+1 UPS+2 DATA PHONE FACE PLATE | 750 | 1010 |
| 2 | 3179202 | SM-MK 8 Module | 1 MAINS+2 UPS+2 DATA PHONE FACE PLATE | 750 | 1060 |
| 3 | 3179203 | SM-MK 10 Module (Type-1) | 2 MAINS+2 UPS+2 DATA PHONE FACE PLATE | 750 | 1110 |
| 4 | 3179204 | SM-MK 10 Module (Type-2) | 1 MAINS+2 UPS+2 DATA PHONE FACE PLATE 1 USB CHARGE+ 1 VGA ADAPTER | 750 | 1110 |
| 5 | 3177545 | SM-MK 10 Module (Type-3) | 1 MAINS+2 UPS+2 DATA PHONE FACE PLATE 1 USB CHARGE+ 1 HDMI ADAPTER | 750 | 1110 |
| 6 | 3179205 | SM-MK 10 Module (Type-4) | 1 MAINS+2 UPS+2 DATA PHONE FACE PLATE 1 USB CHARGE+1 USB ADAPTER | 750 | 1110 |

^(*)Dimensions may be customised if required. (hmax = 120cm)


▶E-Line Smart SM-K / COLUMN TYPE




| | | COLUMN TYPE ST | TANDARD PRODUCT HARDWARE TABLE | | | |
|----|------------|----------------------------|---|-----------|-----------|-----------|
| No | Order Code | Model | Equipment | A (mm) | B (mm) | C (mm) |
| 1 | 3179206 | SM-K 6 Module | 1 MAINS+1 UPS+2 DATA PHONE FACE PLATE | 750 | 2800 | 2900 |
| 2 | 3179207 | SM-K 8 Module | 1 MAINS+2 UPS+2 DATA TEL FACE PLATE | 750 | 2800 | 2900 |
| 3 | 3179208 | SM-K 10 Module (Type-1) | 2 MAINS+2 UPS+2 DATA TEL FACE PLATE | 750 | 2800 | 2900 |
| 4 | 3179209 | SM-K 10 Module (Type-2) | 1 MAINS+2 UPS+2 DATA TEL FACE PLATE 1 USB CHARGE+ 1 VGA ADAPTER | 750 | 2800 | 2900 |
| 5 | 3177544 | SM-K 10 Module (Type-3) | 1 MAINS+2 UPS+2 DATA TEL FACE PLATE 1 USB CHARGE+ 1 HDMI ADAPTER | 750 | 2800 | 2900 |
| 6 | 3179210 | SM-K 10 Module (Type-4) | 1 MAINS+2 UPS+2 DATA TEL FACE PLATE 1 USB CHARGE+1 USB ADAPTER | 750 | 2800 | 2900 |

^(*)Dimensions may be customised if required (hmax=120 cm). (hmax = 600cm)

►E-Line Smart SM-MK (Mini Column) and SM-K (Column) Type floor and suspended ceiling plate







SM-K / MK Base Plate (PC/ABS, V2 (Flame Retardant Class), HF (Halojen Free))

ELINESMART CABLE ORGANIZER






To connect strong current, weak current and multimedia cables from

the flooring to the desks or work environments:

- Flexible and aesthetic solution
- Produced with Halogen-Free plastic material
- Standard size = 75 cm



▶▶ DUAL USB CHARGING DEVICE









Samsung Galaxy S8 Plus Charge Duration (0%-100%) 1 hour 45 minutes Iphone 7 Plus Charge Duration (0%-100%) 1 hour 45 minutes

Maximum constant operation voltage:220-230 V, 50/60 Hz.Output current:Two port total 2,1 A

Input current :5V DC

Maximum operating temperature.....:125 °C (at 25 ° environment temperature) (Documented with test reports.)

Dimensions:45x22x43,5 mmWeight:32grColor:White/Black

Body...:Polaycarbonate (PC), Glow-wire 600 °C

▶▶ SPD SURGE PROTECTION DEVICE



Compact Multi-Pole SPD

MPE Mini & MPE Mini LED

Class III • Type 3

Usage :Cable ducts and cable outputs

Network Systems :TN

Protection Mode :L-PE, L-N, N-PE Fluctuation Rate :Ucc/Icw= 6kV/3kA

Imax= 3kV (8/20µs)

ITITIAL S SKV (6/2)

IEC/EN Category :Class III / Type 3

Protection Elements :MOV and GDT

Safety :Warning; LED

Body :Compact design

Compatibility :IEC 61643-11:2011 EN 61643-11:2012

Maximum constant operation voltage :275 V - 50/60 Hz

Voltage protection rates (L, N-PE) :1,7 kV Voltage protection rates (L, N) :1,5 kV Short circuit current protection rate :1kA :MCB/B 16A Supporting fuse. 8/20µs short circuit current rate... :3kA 1.2/50µs open circuit current rate :6kV Operating temperature range :-40°C / +85°C Humidity range in operating environment... :5% - 95%

Protection level :IP20

:"Metal Oxide Varistor" and "Gas Tube" are technological builds. Includes green LED indicator for

protection term is valid. When the protection term is expired, green LED will extinguish.

...:With Akulon Ultraflow K-FKG S6 (PA 6) plastic protection with UL-94 V0 Fire Retardant

Rate under

Certification and standards aluminium cover

:CE

IEC 61643-11:2011 EN 61643-11:2012

■These products are not sold separately but provided with the product if required.

Body.

Protection technology





A - ENERGY MODULES

| Product Picture | Number of Modules | Product Definition | Order Code |
|-----------------|-------------------|---|------------|
| (%) | 2 | Modular Grounding Socket (Mains), German Standard, 45x45mm, 45° Angled, Child Protected, White, Single | 1004270 |
| | 4 | Modular Grounding Socket (Mains), German Standard, 45x45mm, 45° Angled, Child Protected, White, Double | 1004272 |
| | 6 | Modular Grounding Socket (Mains), German Standard, 45x45mm, 45° Angled, Child Protected, White, Triple | 1003482 |
| | 8 | Modular Grounding Socket (Mains), German Standard, 45x45mm, 45° Angled, Child Protected, White, Quadruple | 1004243 |
| | 2 | Modular Grounding Socket (Mains), French Standard, 45x45mm, 45° Angled, Child Protected, Red, Single | 1004271 |
| | 4 | Modular Grounding Socket (Mains), French Standard, 45x45mm, 45° Angled, Child Protected, Red, Double | 1004273 |
| | 6 | Modular Grounding Socket (Mains), French Standard, 45x45mm, 45° Angled,Child Protected, Red, Triple | 1003483 |
| | 8 | Modular Grounding Socket (Mains), French Standard, 45x45mm, 45° Angled, Child Protected, Red, Quadruple | 1004242 |
| • | 1 | Modular On-Off Switch, 220V, 10A, Illuminated, 22,5x45 mm, White Body | 1016315 |
| 11 | 1 | Dual USB Charge Adapter 2 Ports, Entry 100-240 VAC, 50-60 Hz, Output 5 VDC – 2100mA, 22,5x45mm, White/ Black | 2080363 |

[■]For standard products and unless specified, energy sockets are NE-AD , USB Charger adapter is imported by EAE. ■Please call us for different codes.





B - ACTIVE NETWORK PRODUCTS

| Product Picture | Number of Modules | Product Definition | Order Code |
|-----------------|----------------------|--|------------|
| | - | UTP Cat-6, RJ45 Keystone Jack, Data, White and Black | 1004334 |
| 1 | - | Cat-3, RJ11, 4 contacts, Keystone Jack, Telephone, White and Black | 1004337 |
| | 1 | HDMI Adapter, 22,5x45 mm, Female-Female, 90° angled, with screw, White and Black | 1016317 |
| | 1 | USB 3.0 Adapter, 22,5x45 mm, Female-Female, 90° angled, with screw, White and Black | 1016318 |
| | 1 | VGA Adapter, 22,5x45 mm, Female-Female, 90° angled, with screw, White and Black | 1016319 |

C - PASSIVE NETWORK PRODUCTS

| Product Picture | Number of Modules | Product Definition | Order Code |
|-----------------|----------------------|---|------------|
| | 1 | Luxury Model Faceplate, Spring Cover, 22,5x45 mm, Transparent Protected Label Place, White | 1004186 |
| | 1 | Blind Plastic Cover, 22.5x45, White | 1004246 |
| | 2 | Blind Plastic Cover, 45x45, White | 1002612 |
| 1 | 1 | USB Faceplate, 22,5x45 mm, White and Black | 1016320 |
| 1 | 1 | HDMI Faceplate, 22,5x45 mm, White and Black | 1016321 |
| | 1 | VGA Faceplate, 22,5x45 mm, White and Black | 1016322 |

Active and passive network products, for standard products and unless specified, energy sockets are NE-AD, USB Charger adapter is imported by EAE.

Please call us for different codes.

▶ GENERAL STRUCTURE AND CHARACTERISTICS OF SOKET MODULES



FITTED OFFICE SOCKET BLOCKS

- 1. The body is made of aluminium material and is painted with anodic or electrostatic powder paint system in white and black as colour alternatives.
- 2. Side plastic covers are manufactured of polycarbonate (PC) and meets "halogen free" and glow wire test conditions according to IEC 60965 and they are in "V0" flame retardant proof class according to Ul94.
- 3. Free type standard products may be mounted to the desk by means of appropriate feet available on them if necessary.
- 4. Free type standard products may be screwed inside and/ or under the desk through screw holes on the side covers if necessary.
- 5. Covers of built-in products are opened/ closed mechanical (push open- push close) system and covers may be opened up to 90° in maximum in order to prevent breakage. Cable inlets and outlets of cover are of brush type andbrushes are made of PA6 materials. The design allows covers to close easily regardless of whatever plug or adapter is connected to the socket; and when the cover is in closed position, the product will be at a maximum height of 2 mm to the desk surface.
- 6. Cylindrical type products have a body with "push-open" system and a brake system so that the product will not drop off to the ground when it is wide open. It is designed in a manner that when plugs are connected, it may go back to its nest inside the desk thanks to its elevator mechanism and spring cover structure so that only cable will remain and appear on the desk.
- 7. Standard products that can be mounted to the desk are positioned at a specific angle for easy use; and there is amoveable blanketing plate in harmony with the body at the back of the product which protects cable inlets and outlets.
- 8. İnside the product and in a separate chamber, there is a connector (electric terminal) connection apparatus and an interlocking, screw free connection for each conductor. Moreover, this connector tolerates and bears the traction and tensile loads of cables thank to a cable tightening clips fixed on it.
- 9. Connection of power sockets mounted to the product is via H07Z1-K with a cross section of 2.5mm or, upon request, 1.5mm cross-section. It is equipped with such connectors separately for UPS and Network circuits which can bear at least 16A load and connected by means of screwed and interlocking type.
- 10. Grounding contact screw and grounding connector fixed to the product's aluminium body is cabled with H07Z1-K cable with a cross section of 2.5mm to ensure body protection.
- 11. Socket mounting part is integrated to the body and every brand and universal and modular type is designed compatible with the installation of power sockets with a size of 45x45mm (2 module) and weak current and multimedia socket at a size of 45x22.5mm (1 module).
- 12. Mains and UPS sockets are 250V AC and 16A with 45° angle and spiked characteristicb "White" grounding sockets of German standard are used in mains circuit while "red" grounding sockets of French standard are used in UPS circuit. Phase-neutral-ground bridges of double, triple and quadruple socket systems are secured in themselves by means of brass bar.
- 13. For data cable connections, spring cover and label window "face plate" is used that is compatible with Cat-6 UTP "keystone jack" structure.
- 14. For telephone cable connections, spring cover and label window "face plate" is used that is compatible with Cat-3 "keystone jack" structure.
- 15. Socket mounting part is also compatible with the mounting/ installation of all standard and modular (45x45 mm and/ or 45x22.5mm) USB charging units, USB adapter, VGA adapter, HDMI adapter etc and they can be used together with all brands.
- 16. 45x22.5mm (1 module) size blind covers compatible with the body are used between different strong and weak current sockets and after the last socket but before the termination cover
- 17. For cable outputs on the desk, cable organized and protective plastic backbone Conduits with flexible structure and "halogen free" are used.





CE DECLARATION OF CONFORMITY

Product Group E-LINE SMART Equipped Desk Socket Blocks

Manufacturer EAE Elektrik Asansor End. Inşaat San. ve Tic. A.S.

Akcaburgaz Mahallesi, 3114. Sokak,

No:10, 34522 Esenyurt - İstanbul

We confirm that products or product group mentioned above manufactured in EAE Facilities conform to standards and regulations listed below.

Standard:

IEC 60670-1

"Boxes and enclosures for electrical accessories for household and similar fixed electrical installation – Part 1: General requirements"

CE - Directive:

2014/35/EU "The Low Voltage Directive"

Technical Document Preparation Official:

EAE Elektrik Asansor End. Insaat San. ve Tic. A.S. Akcaburgaz Mahallesi, 3114. Sokak, No:10 34522 Esenyurt-Istanbul

Emre GÜRLEYEN

Date

Document Authorized Signatory

08/03/2021

Elif Gamze KAYA OK Genel Müdür Yardımcısı





| Member List | Type Pcs. | | | | | |
|-------------|-----------|---------|---------|------------|-----------------|--|
| | Serial | Company | Project | Project No | Date Signature: | |
| | | | | | | |
| | | | | | | |
| | | | | | EVE | |





| | | Member List | |
|--|-----------------|-------------|------|
| | Serial No | Туре | Pcs. |
| | | | |
| | Company : | | |
| | Project : | | |
| | Project No : | | |
| | | | |
| EAE | bate Signature: | | |
| Please duplicate this page for your own use. | / | | |

PRODUCT TYPES

Please visit our website for the updated version of our catalogues.

www.eaeelectric.com

MENISTAN BULGARISTANISVICRE FAS ISPANYA MOLDOVYAIRAK ISVIÇRE BREZILYASLOVENYA UNDUNINGEN SULDEN BREZILYASLOVENYA ISVIÇRE BREZILYASLOVENYA SULDEN BREZILYASLOVENYA ISVIÇRE BREZILYASLOVENYA SILANKA NLEENA B.BRITANYA IRLANDA. MADAGASKAR SILANKA NLEENA B.BRITANYA IRLANDA. AVUSTURYA IZLANDA, GÜRCISTAN FAS TANZANYA IRLANDA ISPANYA IZLANDA, GÜRCISTAN FAS TANZANYA IRLANDA ISPANYA GÜNEY AFRIKA SUUDI ARABISTANBANGLADES BULGARISTAN MOLDOVYA HOLLANDA AVUSTURYA CEK CUMHURIVETHIRVATISTAN MOLDOVYA MORITYUS IÇREBREZILYA BELÇIKA FINLANDIYA IRLANDA LÜKSEMBURG GÜRCISTAN HIRVATISTAN SUUDI ARABISTANBUL GARISTANMA KEDON

BUSBAR ENERGY DISTRIBUTION SYSTEMS CABLE TRAYS TROLLEY BUSBAR ENERGY DISTRIBUTION SYSTEMS INDOOR SOLUTIONS SUPPORT SYSTEMS

TANDANIMARKAJRAK ISVIÇRE BREZILYASLOVENYA
KAMERUNRUANDĀ
LBRITANYA IRLANDA, KENYA MADAGASKAR
ILBRITANYA IRLANDA, AVUSTURYA
AN FAS TANZANYA IRLANDA, AVUSTURYA
BUNEY KORE ETIYOPYA ALMANYA ISPANYA
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
MORITYUS SIRBISTAN
BELÇIKA PAKISTAN FAS TANZANYA BREZILYASLOVENYA MEKSIK
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MADAGASKAR NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MAZANYA BREÇİKA NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MAZANYA BREÇİKA NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MAZANYA BREÇİKA NORV
LÜBNA NTANZANYA ESTONYA GÜNEY KORE MAZANYA BREÇİKA NORV
LÜBNA NTANZANYA ÇINKEN ÇINKEN KAMERUNDA KONGOLONYA K

EAE Elektrik A.S. Akcaburgaz Mahallesi, 3114. Sokak, No:10 34522 Esenyurt - Istanbul - TURKEY Tel: +90 (212) 866 20 00 Fax: +90 (212) 886 24 20

EAE Elektrik Gebze Fabrika Gebze IV Istanbul Makine ve Sanayicileri Organize Bolgesi 6.Cadde No.2 Demirciler Koyu Dilovasi - KOCAELI - TURKEY Tel: +90 (262) 502 05 65 Fax: +90 (262) 502 05 70

Please visit our website for the updated version of our catalogues. www.eaeelectric.com



Catalogue 31-EN. / Rev 05 1000 pcs 31/05/2021 S.S.

We reserve the right to make changes in the values given in the catalogue.